

## A34 Warning Sign – Junction with a Minor Road on the Right, 70 cm, Class I

Class I (EGP) Road Signs

Signs compliant with SR 1848-1:2024



### AT A GLANCE

- Warning sign A34 "Junction with a minor road", to SR 1848-1:2024.
- 70 cm triangle in 1 mm galvanised steel sheet, 2 kg.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: clamps for Ø48 mm posts and bolts with nuts.

|              |                                            |
|--------------|--------------------------------------------|
| Product code | <b>A34</b>                                 |
| Category     | <b>Metal Road Signs</b>                    |
| Weight       | <b>2 kg</b>                                |
| Compliance   | <b>Class I (EGP) Road Signs</b>            |
| Compliance   | <b>Signs compliant with SR 1848-1:2024</b> |



This product on [attotrafic.ro](https://attotrafic.ro/en_US/products/a34-intersec-tie-cu-drum-fara-prioritate-70-cm-clasa-i)  
[https://attotrafic.ro/en\\_US/products/a34-intersec-tie-cu-drum-fara-prioritate-70-cm-clasa-i](https://attotrafic.ro/en_US/products/a34-intersec-tie-cu-drum-fara-prioritate-70-cm-clasa-i)

### Technical specifications

|                      |                                                                  |
|----------------------|------------------------------------------------------------------|
| SR 1848-1 code       | A34                                                              |
| Name in the standard | Junction with a minor road                                       |
| Type                 | Warning road sign                                                |
| Shape and colours    | Equilateral triangle, red border, white background, black symbol |
| Size                 | 70 cm side (normal format)                                       |
| Red border           | 60 mm                                                            |
| Material             | Galvanised steel sheet, 1 mm                                     |
| Construction         | Rounded corners, pressed edges, no sharp edges                   |
| Painting             | Electrostatic                                                    |

|                                  |                                                                    |
|----------------------------------|--------------------------------------------------------------------|
| Retroreflective sheeting         | Class I (RA1)                                                      |
| Retroreflection (white, 0.2°/5°) | 70 cd/(lx·m²)                                                      |
| Sheeting service life            | 7 years                                                            |
| Weight                           | 2 kg                                                               |
| Fixings included                 | Clamps and bolts with nuts                                         |
| Post diameter                    | Ø48 mm (Ø60 mm on request)                                         |
| Standards                        | SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011 |

## Description

The A34 announces a minor road joining yours from the right. Vehicles on it must give way to you, but it helps to know in advance that they may appear.

### Where it goes, under SR 1848-1:2024

It goes outside built-up areas, on the approach to a junction with a minor road, if the junction is not already signed with advance direction signs F1, F1a, F2 or F13. It is not used at junctions with dirt roads. The minor roads must have the B1 “Give way” or the B2 “Stop” sign. The symbol shows the layout: here, the side road joins from the right.

How far before the hazard: in a built-up area, 50 m at most; outside it, between 100 and 250 m; on a motorway or expressway, between 500 and 1,000 m, with the P4 panel underneath. When site conditions call for a longer distance, the P4 is used anywhere.

### Technical data

- equilateral triangle with a 70 cm side (normal format, SR 1848-2), 60 mm red border, white background, black symbol;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted;
- class I retroreflective sheeting (RA1), with a 7-year service life;
- weight: 2 kg;
- fixings included: clamps for Ø48 mm posts and bolts with nuts;
- compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

### Mounting

The sign comes with clamps for Ø48 mm posts and bolts with nuts. Clamps for Ø60 mm posts are available on request. It goes on the right-hand side of the road, with its bottom edge 1.50–2.50 m up and its inner edge 0.50–2.0 m from the platform; on roads with two or more lanes each way, repeating it on the left is recommended. No more than three signs go on the same post.

The 70 cm triangle is the normal format in SR 1848-2, meant for county and local roads, streets and private roads open to public traffic. National roads call for large 90 cm signs, and motorways for very large 120 cm ones.