

C21 Prohibition Sign – Minimum Distance of 70 m between Vehicles, Ø60 cm, Class I

Class I (EGP) Road Signs

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Prohibition or restriction sign C21 "Minimum safety distance of 70 m between motor vehicles", to SR 1848-1:2024.
- 60 cm diameter disc, normal format, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	C21-70
Category	Metal Road Signs
Weight	3 kg
Compliance	Class I (EGP) Road Signs
Compliance	Signs compliant with SR 1848-1:2024



This product on attotrafic.ro
https://attotrafic.ro/en_US/products/c21-distanta-minima-de-70-m-intre-autovehicule-o60-cm-clas-a-i

Technical specifications

SR 1848-1 code	C21
Name in the standard	Minimum safety distance of 70 m between motor vehicles
Type	Prohibition or restriction road sign
Shape and colours	White disc with a red border, with the outlines of two cars and the 70 m distance between them
Value shown	70 m
Size	60 cm diameter
Format (SR 1848-2)	Normal

Red border	60 mm
Digit height	75 mm digits
Material	Galvanised steel sheet, 1 mm
Construction	Pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	3 kg
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The C21 requires a gap of at least 70 m between moving motor vehicles, for example on long bridges or in tunnels. The sign shows two cars and the distance between them.

When class I is used

Class I (RA1) sheeting returns 70 cd/(lx·m²) for white to the driver and has a 7-year service life, enough on roads where headlights are the only light: local, minor and private roads or quiet streets. In areas with street lighting, shop windows, advertising and dense urban traffic, however, SR 1848-2 requires prismatic class 2 or 3 sheeting.

Where it goes, under SR 1848-1:2024

It goes at the start of a section where a safety gap must be kept between moving motor vehicles, together with the P8 additional panel showing the length of the section. It is repeated every 1.5–2.0 km and after every junction; without the panel, it applies up to the first junction.

Technical data

- 60 cm diameter disc (normal format, SR 1848-2): white with a red border, with the outlines of two cars and the 70 m distance between them;
- 1 mm galvanised steel sheet, with pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 3 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The 60 cm diameter is the normal format in SR 1848-2, for county and local roads, streets and private roads open to public traffic. National roads call for the large Ø80 cm format and motorways for the very large Ø100 cm one; the standard forbids using a smaller format than the road category requires.