C27 Prohibition Sign – Speed Limit 5 km/h, Ø40 cm, Class I

Class I (EGP) Road Signs | Signs compliant with SR 1848-1:2024



AT A GLANCE

- Prohibition or restriction sign C27 “Maximum speed limit (5 km/h)”, to SR 1848-1:2024.
- 40 cm diameter disc, small format, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts, with bolts and nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	**C27-5_40_I**
Category	**Non-STAS**
Weight	**2 kg**
Compliance	**Class I (EGP) Road Signs**
Compliance	**Signs compliant with SR 1848-1:2024**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/c27-limitare-de-viteza-5-km-h-o40-cm-clasa-i

Technical specifications

SR 1848-1 code	C27
Name in the standard	Maximum speed limit (5 km/h)
Type	Prohibition or restriction road sign
Shape and colours	White disc with a red border and the value 5 km/h in black
Value shown	5 km/h
Size	40 cm diameter
Format (SR 1848-2)	Small
Material	Galvanised steel sheet, 1 mm

Construction	Pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	2 kg
Fixings included	2 clamps, with bolts and nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The C27 showing 5 km/h sets the speed limit for the section ahead: the value in black on a white background, inside a red border, may not be exceeded until the sign that ends the limit. The Ø40 cm disc is the small format in SR 1848-2, used on low-traffic minor roads.

When class I is used

Class I (RA1) sheeting returns 70 cd/(lx·m²) for white to the driver and has a 7-year service life, enough on roads where headlights are the only light: local, minor and private roads or quiet streets. In areas with street lighting, shop windows, advertising and dense urban traffic, however, SR 1848-2 requires prismatic class 2 or 3 sheeting.

Where it goes, under SR 1848-1:2024

It goes at the start of a section where the speed shown may not be exceeded. The end of the limit is signed with the C34 (end of speed limit). As needed, it can carry the P27 (ice, frost, snow) or P29 (rain, fog, blizzard) additional panels. Installed with the town entry sign, it applies throughout the town, except where other signs say otherwise.

Like all prohibition signs, it goes right after the junction before the restricted place, so drivers can go round without turning back, and it is repeated after every junction on the section. Exemptions for residents or certain vehicle categories are shown on the P34 and P18 additional panels.

Technical data

- 40 cm diameter disc (small format, SR 1848-2): white with a red border and the value 5 km/h in black;
- 1 mm galvanised steel sheet, with pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 2 kg;
- fixings included: 2 clamps for Ø48 mm posts, with bolts and nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts, with bolts and nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The 40 cm diameter is the small format in SR 1848-2, meant for low-traffic minor roads and for short-term police signing at accident scenes. County and local roads, streets and private roads open to public traffic call for the normal Ø60 cm format: the C27-5. In car parks and private premises closed to public traffic the standard is not mandatory, so the small format is enough there.


Drawings and details · 1/3

C27 – Limitare de viteză

Maximum speed limit

Ø40 cm · dimensiunile feței indicatorului

Ø40 cm · sign face dimensions



Dimensiuni SR 1848-2 (mm)
SR 1848-2 dimensions (mm)

Ø40 cm
D = 400 · a = 50 · h = 175
drumuri vicinale cu trafic redus
low-traffic local access roads

Ø60 cm
D = 600 · a = 60 · h = 260
drumuri județene, comunale, străzi
county and communal roads, streets

Ø80 cm
D = 800 · a = 80 · h = 345
drumuri naționale
national roads

Ø100 cm
D = 1000 · a = 100 · h = 435
autostrăzi
motorways

Fond alb, chenar roșu a; cotele sunt ale feței retroreflectorizante.
White background, red border a; dimensions of the retroreflective face.

Panoul suport depășește fața cu 5–10 mm (SR 1848-2, 6.1).
The backing panel is 5–10 mm larger than the face (SR 1848-2, 6.1).


Formatul se alege după categoria drumului (SR 1848-2, 5.2).
The format follows the road category (SR 1848-2, 5.2).

Cifrele și unitățile: scriere tip „îngust” (ca în figurile SR 1848-1:2024).
Digits and units: narrow type (as in the SR 1848-1:2024 figures).

Scriere SR 1848-3: tip „îngust”, H = 175 mm.
SR 1848-3 lettering: narrow type, H = 175 mm.

Sursa: SR 1848-2:2011, tab. 3, tab. 4 și tab. 5.
Source: SR 1848-2:2011, table 3, table 4 and table 5.


Drawings and details · 2/3



Drawings and details · 3/3

Prindere cu canal și colier, stâlp Ø48 mm

Channel and clamp fixing, Ø48 mm post



1 Canal de prindere din aluminiu (pe spatele panoului)
Aluminium fixing channel (on the back of the panel)

2 Șurub M8 × 35 cu cap pătrat, zincat (2 buc.)
M8 × 35 square-head bolt, galvanised (2 pcs)

3 Colier Ø48 mm din tablă zincată
Ø48 mm clamp, galvanised steel

4 Piuliță M8 zincată (2 buc.)
M8 nut, galvanised (2 pcs)

Set pentru un punct de prindere. Pentru stâlp Ø60 mm, colierele se livrează la cerere.
Set for one fixing point. Clamps for Ø60 mm posts are available on request.