
D7 Mandatory Sign – Roundabout, Ø80 cm, Class II

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Mandatory sign D7 “Roundabout”, to SR 1848-1:2024.
- 80 cm diameter blue disc with three white arrows arranged in a circle, in 1 mm galvanised steel sheet.
- Class II (RA2) prismatic sheeting, guaranteed 10-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	**D7_II**
Category	**Metal Road Signs (Class II)**
Weight	**5.5 kg**
Compliance	**Signs compliant with SR 1848-1:2024**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/d7-intersectie-cu-sens-giratoriu-o80-cm-clasa-ii

Technical specifications

SR 1848-1 code	D7
Name in the standard	Roundabout
Type	Mandatory road sign
Shape and colours	80 cm diameter blue disc with three white arrows arranged in a circle
Size	Ø80 cm
Format (SR 1848-2)	Large
Material	Galvanised steel sheet, 1 mm
Construction	Pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint

Retroreflective sheeting	Class II (RA2), prismatic, UV-resistant
Retroreflection (white, 0.2°/5°)	250 cd/(lx·m²)
Sheeting service life	10 years (SR 1848-2)
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The blue disc with three white arrows in a circle, in the large Ø80 cm format with class II prismatic sheeting. It marks the entry to roundabouts on national roads and at town entrances, where it can be seen from far away, even among street lights.

Why class II

Class II means RA2 prismatic sheeting, which sends back three to four times more light than class I sheeting. It matters on fast roads and wherever the sign is seen at an angle, and in areas with street lighting, shop windows and advertising SR 1848-2 explicitly requires it, alongside class 3. The sheeting has a guaranteed 10-year service life.

Where it goes, under SR 1848-1:2024

It goes at the entry to the circulatory carriageway of the roundabout, on the same post as the B1 (Give way), and is preceded by the A38 (Roundabout ahead). On a national road, in class II, the full set is the A38_II (90 cm triangle), the B1_II (120 cm triangle) and this Ø80 cm disc.

Technical data

- 80 cm diameter blue disc with three white arrows arranged in a circle;
- 1 mm galvanised steel sheet, with pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class II (RA2) prismatic retroreflective sheeting, resistant to UV and weathering, with a guaranteed 10-year service life;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The 80 cm diameter is the large format in SR 1848-2, required on national roads; motorways use the very large 100 cm format. County and local roads, streets and private roads open to public traffic only need the normal Ø60 cm format: the class I sheeting version is the D7.


Drawings and details · 1/3

D7 – Intersecție cu sens giratoriu

Roundabout

Ø80 cm · dimensiunile feței indicatorului

Ø80 cm · sign face dimensions



Dimensiuni SR 1848-2 (mm)
SR 1848-2 dimensions (mm)

Ø40 cm
D = 400
drumuri vicinale cu trafic redus
low-traffic local access roads

Ø60 cm
D = 600
drumuri județene, comunale, străzi
county and communal roads, streets

Ø80 cm
D = 800
drumuri naționale
national roads

Ø100 cm
D = 1000
autostrăzi
motorways


Fond albastru, simbol alb; cotele sunt ale feței retroreflectorizante.
Blue background, white symbol; dimensions of the retroreflective face.

Panoul suport depășește fața cu 5–10 mm (SR 1848-2, 6.1).
The backing panel is 5–10 mm larger than the face (SR 1848-2, 6.1).

Formatul se alege după categoria drumului (SR 1848-2, 5.2).
The format follows the road category (SR 1848-2, 5.2).

Sursa: SR 1848-2:2011, tab. 3.
Source: SR 1848-2:2011, table 3.


Drawings and details · 2/3



Drawings and details · 3/3

Prindere cu canal și colier, stâlp Ø48 mm

Channel and clamp fixing, Ø48 mm post



1 Canal de prindere din aluminiu (pe spatele panoului)
Aluminium fixing channel (on the back of the panel)

2 Șurub M8 × 35 cu cap pătrat, zincat (2 buc.)
M8 × 35 square-head bolt, galvanised (2 pcs)

3 Colier Ø48 mm din tablă zincată
Ø48 mm clamp, galvanised steel

4 Piuliță M8 zincată (2 buc.)
M8 nut, galvanised (2 pcs)

Set pentru un punct de prindere. Pentru stâlp Ø60 mm, colierele se livrează la cerere.
Set for one fixing point. Clamps for Ø60 mm posts are available on request.