

G10 Information Sign – First-Aid Post, 50×65 cm, Class I

Class I (EGP) Road Signs

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Information sign G10 "First-Aid Post", to SR 1848-1:2024.
- Blue rectangle, 50 × 65 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code **G10**

Category **Metal Road Signs**

Weight **3.2 kg**

Compliance **Class I (EGP) Road Signs**

Compliance **Signs compliant with SR 1848-1:2024**



This product on attotrafic.ro

https://attotrafic.ro/en_US/products/g10-post-de-prim-ajutor-50x65-cm-clasa-i

Technical specifications

SR 1848-1 code	G10
Name in the standard	First-aid post
Type	Information road sign
Shape and colours	Blue rectangle with a white field showing a red cross
Size	50 × 65 cm
White field	40 × 35 cm
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant

Retroreflection (white, 0.2°/5°)	70 cd/(lx·m ²)
Sheeting service life	7 years
Weight	3.2 kg
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The G10 shows where first aid can be had: the red cross on the white field of the blue rectangle is recognised at once.

When class I is used

Class I (RA1) sheeting returns 70 cd/(lx·m²) for white to the driver and has a 7-year service life, enough on roads where headlights are the only light: local, minor and private roads or quiet streets. In areas with street lighting, shop windows, advertising and dense urban traffic, however, SR 1848-2 requires prismatic class 2 or 3 sheeting.

Where it goes, under SR 1848-1:2024

It goes near a first-aid post, a clinic and similar. If the post is on a side road, a white arrow is drawn at the bottom of the sign, with the distance to the post above it.

As a general rule, information signs go in the area of the place they indicate. Where needed, they are signed in advance with an identical sign at least 50 m ahead in built-up areas and at least 150 m outside them, with the distance in white at the bottom or on the P1 additional panel.

Technical data

- 50 × 65 cm panel: blue rectangle with a white field showing a red cross;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 3.2 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 50 × 65 cm, white field 40 × 35 cm. These are the dimensions SR 1848-2 sets for this sign.