

G31 Information Sign – Parking, Max. 2 Hours, 50×65 cm, Class I

Class I (EGP) Road Signs



AT A GLANCE

- Information sign G31 "Parking, Max. 2 Hours".
- Blue rectangle, 50 × 65 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	G31o
Category	Non-STAS
Weight	3.2 kg
Compliance	Class I (EGP) Road Signs



This product on [attotrafic.ro](https://attotrafic.ro/en_US/products/g31-parcare-cu-durata-maxima-de-2-ore-50x65-cm-clasa-i)
https://attotrafic.ro/en_US/products/g31-parcare-cu-durata-maxima-de-2-ore-50x65-cm-clasa-i

Technical specifications

Type	Information road sign (version outside SR 1848-1:2024)
Shape and colours	Blue rectangle with the letter P and the words MAX. 2 ORE in white
Size	50 × 65 cm
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	3.2 kg
Fixings included	2 clamps, 4 bolts with nuts

Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-2:2011
Marking	CE

Description

This is a version of the G31 (parking): below the letter P it reads MAX. 2 ORE (max. 2 hours), the maximum parking time. The standard lists the information that may appear below the letter P, and this is not among it, so this version is used mainly in private car parks and premises.

When class I is used

The sign has class I (RA1) retroreflective sheeting: 70 cd/(lx·m²) for white and a 7-year service life. It is the economical choice for places without many light sources, such as local, minor and private roads or streets without strong lighting. Where there is street lighting, shop windows or advertising, SR 1848-2 requires prismatic class 2 or 3 sheeting, which stands out better against a lit background.

Where it goes, under SR 1848-1:2024

It goes before places for parking or standing vehicles. The bottom of the sign may show: an arrow towards the car park and, where needed, the distance; a car symbol in the position in which it may park relative to the kerb; the P15 or P16 (pay parking) symbol; a text such as "Reserved for vehicles with a badge, CD"; the outline of a vehicle category, when the car park is reserved for it alone.

Technical data

- 50 × 65 cm panel: blue rectangle with the letter P and the words MAX. 2 ORE in white;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 3.2 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; sheet, sheeting and construction to SR EN 12899-1:2007 and SR 1848-2:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 50 × 65 cm.