

G31 Information Sign – No Parking (Crossed P), 50×65 cm, Class I

Class I (EGP) Road Signs



AT A GLANCE

- Information sign G31 "No Parking (Crossed P)".
- Blue rectangle, 50 × 65 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code **G31i**

Category **Non-STAS**

Weight **3.2 kg**

Compliance **Class I (EGP) Road Signs**



This product on [attotrafic.ro](https://attotrafic.ro/en_US/products/g31-parcare-interzisa-p-taiat-50x65-cm-clasa-i)
https://attotrafic.ro/en_US/products/g31-parcare-interzisa-p-taiat-50x65-cm-clasa-i

Technical specifications

Type	Information road sign (version outside SR 1848-1:2024)
Shape and colours	Blue rectangle with the letter P crossed by a red diagonal bar
Size	50 × 65 cm
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	3.2 kg
Fixings included	2 clamps, 4 bolts with nuts

Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-2:2011
Marking	CE

Description

This is a version of the G31 (parking): below the letter P nothing is added: the letter P is crossed by a red diagonal bar. It is not an SR 1848-1:2024 sign: on public roads, a parking ban is signed with the C36 (no parking). This version is used on private premises and in private car parks.

When class I is used

Class I means RA1 retroreflective sheeting, with 70 cd/(lx·m²) for white and a 7-year service life. It suits places where the sign does not compete with other lights: roads and streets without strong lighting, local, minor and private roads. In areas with many light sources, such as streets with public lighting, shop windows and advertising, SR 1848-2 requires prismatic class 2 or 3 sheeting, because a class I sign gets lost against the background there.

Where it goes

It goes at the entrance to the part of a car park or premises where the owner does not allow parking, in plain view of those coming in. On public roads the C36 (no parking) or C37 (no stopping) is used instead.

Technical data

- 50 × 65 cm panel: blue rectangle with the letter P crossed by a red diagonal bar;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 3.2 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; sheet, sheeting and construction to SR EN 12899-1:2007 and SR 1848-2:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 50 × 65 cm.