

G31 Information Sign – Car Parking, 50×65 cm, Class I

Class I (EGP) Road Signs



AT A GLANCE

- Information sign G31 "Car Parking", to SR 1848-1:2024.
- Blue rectangle, 50 × 65 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code **G31a**

Category **Non-STAS**

Weight **3.2 kg**

Compliance **Class I (EGP) Road Signs**



This product on [attotrafic.ro](https://attotrafic.ro/en_US/products/g31-parcare-pentru-autoturisme-50x65-cm-clasa-i)
https://attotrafic.ro/en_US/products/g31-parcare-pentru-autoturisme-50x65-cm-clasa-i

Technical specifications

SR 1848-1 code	G31
Name in the standard	Parking
Type	Information road sign
Shape and colours	Blue rectangle with the letter P and the outline of a car, in white
Size	50 × 65 cm
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years

Weight	3.2 kg
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

This is a version of the G31 (parking): below the letter P there is the outline of a car, reserving the car park for cars. SR 1848-1:2024 allows this information at the bottom of the sign.

When class I is used

Class I means RA1 retroreflective sheeting, with 70 cd/(lx·m²) for white and a 7-year service life. It suits places where the sign does not compete with other lights: roads and streets without strong lighting, local, minor and private roads. In areas with many light sources, such as streets with public lighting, shop windows and advertising, SR 1848-2 requires prismatic class 2 or 3 sheeting, because a class I sign gets lost against the background there.

Where it goes, under SR 1848-1:2024

It goes before places for parking or standing vehicles. The bottom of the sign may show: an arrow towards the car park and, where needed, the distance; a car symbol in the position in which it may park relative to the kerb; the P15 or P16 (pay parking) symbol; a text such as "Reserved for vehicles with a badge, CD"; the outline of a vehicle category, when the car park is reserved for it alone.

Like all information signs, it has a blue background on ordinary roads and a green one on motorways, and it goes level with the place it indicates. Advance signing, where needed, uses an identical sign at least 50 m ahead in towns or 150 m outside them.

Technical data

- 50 × 65 cm panel: blue rectangle with the letter P and the outline of a car, in white;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 3.2 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 50 × 65 cm.