

G33 Information Sign – Service Complex, 95×100 cm, Class I

Class I (EGP) Road Signs

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Information sign G33 "Service Complex", to SR 1848-1:2024.
- Blue panel, 95 × 100 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 6 clamps for Ø48 mm posts and 12 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code **G33**

Category **Metal Road Signs**

Weight **14.5 kg**

Compliance **Class I (EGP) Road Signs**

Compliance **Signs compliant with SR 1848-1:2024**



This product on attotrafic.ro

https://attotrafic.ro/en_US/products/g33-complex-de-servicii-95x100-cm-clasa-i

Technical specifications

SR 1848-1 code	G33
Name in the standard	Service complex
Type	Information road sign
Shape and colours	Blue panel with four white fields: restaurant, hotel, telephone and car service, and the distance of 200 m
Size	95 × 100 cm
White fields	4 fields of 40 × 35 cm
Distance digit height	6 cm
Material	Galvanised steel sheet, 1 mm

Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	14.5 kg
Fixings included	6 clamps, 12 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The G33 puts the services of a roadside complex on one panel: here a restaurant, hotel, telephone and car service, each in its own white field, with the distance below.

When class I is used

Class I means RA1 retroreflective sheeting, with 70 cd/(lx·m²) for white and a 7-year service life. It suits places where the sign does not compete with other lights: roads and streets without strong lighting, local, minor and private roads. In areas with many light sources, such as streets with public lighting, shop windows and advertising, SR 1848-2 requires prismatic class 2 or 3 sheeting, because a class I sign gets lost against the background there.

Where it goes, under SR 1848-1:2024

It goes before the access to a service complex for road users. The number of fields depends on the number of services, and the opening hours may be written at the bottom. SR 1848-2 gives the panel as 95 × 100 cm for four fields and 140 × 140 cm for nine.

The general rule in SR 1848-1:2024: the information sign stands in the area of the place it shows, and where useful it is signed in advance with an identical sign at least 50 m ahead in towns and 150 m outside them; the distance is written at the bottom in white or on the P1 panel.

Technical data

- 95 × 100 cm panel: blue panel with four white fields: restaurant, hotel, telephone and car service, and the distance of 200 m;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 14.5 kg;
- fixings included: 6 clamps for Ø48 mm posts and 12 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 6 clamps for Ø48 mm posts and 12 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 95 × 100 cm, white fields 4 fields of 40 × 35 cm, distance digit height 6 cm. These are the dimensions SR 1848-2 sets for this sign.