

G5 Information Sign – One-Way Street, Arrow Right, 120×33 cm, Class I

Class I (EGP) Road Signs

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Information sign G5 "One-Way Street, Arrow Right", to SR 1848-1:2024.
- White arrow-shaped panel pointing right, 120 × 33 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	G5d
Category	Metal Road Signs
Weight	5.5 kg
Compliance	Class I (EGP) Road Signs
Compliance	Signs compliant with SR 1848-1:2024



This product on [attotrafic.ro](https://attotrafic.ro/en_US/products/g5-sens-unic-sageata-spre-dreapta-120x33-cm-clasa-i)
https://attotrafic.ro/en_US/products/g5-sens-unic-sageata-spre-dreapta-120x33-cm-clasa-i

Technical specifications

SR 1848-1 code	G5
Name in the standard	One-way traffic
Type	Information road sign
Shape and colours	White arrow-shaped panel pointing right, with a black border and the black words SENS UNIC
Size	120 × 33 cm
Letter height	17.5 cm
Material	Galvanised steel sheet, 1 mm

Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	5.5 kg
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The G5 is the SENS UNIC (one way) arrow panel, black lettering on white, showing from a junction which way the one-way road runs. This version points right.

When class I is used

Class I (RA1) sheeting returns 70 cd/(lx·m²) for white to the driver and has a 7-year service life, enough on roads where headlights are the only light: local, minor and private roads or quiet streets. In areas with street lighting, shop windows, advertising and dense urban traffic, however, SR 1848-2 requires prismatic class 2 or 3 sheeting.

Where it goes, under SR 1848-1:2024

It goes at the junction, parallel to the axis of the one-way road, opposite the road that joins or crosses it. At the entrance to the one-way road the D3 (turn right) or D4 (straight ahead or right) goes, as appropriate.

Like all group G information signs, it is rectangular or square; the background is blue on ordinary roads and green on motorways.

Technical data

- white arrow-shaped panel pointing right, with a black border and the black words SENS UNIC, 120 × 33 cm;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 5.5 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 120 × 33 cm, letter height 17.5 cm. These are the dimensions SR 1848-2 sets for this sign.