

G61 Information Sign – Recommended Speed 60 km/h, 65×65 cm, Class I

Class I (EGP) Road Signs

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Information sign G61 "Recommended Speed 60 km/h", to SR 1848-1:2024.
- Blue square, 65 × 65 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	G61
Category	Metal Road Signs
Weight	3.6 kg
Compliance	Class I (EGP) Road Signs
Compliance	Signs compliant with SR 1848-1:2024



This product on attotrafic.ro
https://attotrafic.ro/en_US/products/g61-viteza-recomandata-60-km-h-65x65-cm-clasa-i

Technical specifications

SR 1848-1 code	G61
Name in the standard	Recommended speed
Type	Information road sign
Shape and colours	Blue square with the figures 60 in white
Size	65 × 65 cm
Digit height	40 cm
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges

Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	3.5 kg
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The G61 recommends a speed, here 60 km/h, so that all vehicles travel at much the same pace and traffic flows smoothly. The white figures on a blue square set it apart from the compulsory C27 limit.

When class I is used

The sign has class I (RA1) retroreflective sheeting: 70 cd/(lx·m²) for white and a 7-year service life. It is the economical choice for places without many light sources, such as local, minor and private roads or streets without strong lighting. Where there is street lighting, shop windows or advertising, SR 1848-2 requires prismatic class 2 or 3 sheeting, which stands out better against a lit background.

Where it goes, under SR 1848-1:2024

It goes at the start of a section where it helps for all vehicles to travel close to the recommended speed, and is repeated after every junction. It is also used on main roads in towns, where traffic is wanted at speeds above the general 50 km/h limit. At the end of the section in town a C27 with the 50 km/h limit is recommended; without it, the recommendation applies up to the first junction.

Information signs neither ban nor require anything: they give useful information about the road and what lies along it. On motorways they have a green background, on other roads a blue one.

Technical data

- 65 × 65 cm panel: blue square with the figures 60 in white;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 3.5 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. The sign must be visible from at least 50 m in built-up areas and 100 m outside them.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 65 × 65 cm, digit height 40 cm. These are the dimensions SR 1848-2 sets for this sign.