Signalling Fence with Sign Panel – Road Works, Red, 150×100 cm

Class I (EGP) Road Signs



AT A GLANCE

- Red 150 × 100 cm fence with a yellow 100 × 50 cm panel.
- On the panel: the road works sign.
- 4 red and white chequered reflective films; side clip for joining.
- 2 threaded sockets for lamps or signs.

Product code	**ATZ 80150-RL**
Category	**Barriers**
Brand	**Atto Trafic**
Weight	**12 kg**
Compliance	**Class I (EGP) Road Signs**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/gard-de-semnalizare-cu-panou-lucrari-rosu-150×100-cm

Technical specifications

Panel Dimensions	100 × 50 cm
Material	PVC, PPC
Color	Red
Reflective	4 reflective sheets
Installation	4 Dowels, 4 Screws

Description

A site fence that explains itself. In the middle of the red 150 × 100 cm fence there is a yellow 100 × 50 cm panel with the road works triangle: the figure with a shovel that every driver and pedestrian recognises.

Where it goes

In front of a trench on the pavement, at the end of a line of fences closing off a work area, at the entrance to a small site. Because the sign is on the fence, you do not need a separate post and base for it.

The fence

- red PVC and PPC frame, 5 cm thick, on two black feet;

- red and white chequered bands top and bottom, 4 reflective films;
- a side clip for attaching to other fences;
- 2 threaded sockets for a warning lamp.

If the direction must be shown too


The same fence comes with two signs on the panel: road works together with keep left (ATZ 80150-ROL) or with keep right (ATZ 80150-RLO).

Drawings and details · 1/5

Dimensiuni
Dimensions

mm

ATZ 80150-RL



lateral
side view


Lungime 150 cm, înălțime 100 cm, grosimea ramei 5 cm; picior de 50 cm. Greutate 12 kg. Abatere admisă ± 5 %.
Length 150 cm, height 100 cm, frame 5 cm thick; 50 cm foot. Weight 12 kg. Tolerance ± 5 %.
Panou PVC spumat de 100 x 50 cm, pe o singură față (măsoară 101 x 52 cm, grosime 3 mm).
100 x 50 cm PVC foam panel on one side (measures 101 x 52 cm, 3 mm thick).
2 socluri filetate Ø32 mm, adânci de 25,5 mm, la 96 cm distanță, pentru lămpi sau indicatoare.
2 threaded Ø32 mm sockets, 25.5 mm deep, 96 cm apart, for lamps or signs.

ATZ 80150-RL dimensions

Drawings and details · 2/5

Detalii
Details


ATZ 80150-RL



Clemă laterală: se prinde de gardul următor
Side clamp: locks onto the next barrier



Soclu filetat Ø32 mm, pentru lampă sau indicator
Threaded Ø32 mm socket for a lamp or sign



Panoul se prinde cu 9 cleme cu șurub, incluse
The panel is held by 9 clamps with screws, included



Picior rotativ de 50 cm, se fixează cu 2 șuruburi
Rotating 50 cm foot, fixed with 2 screws

ATZ 80150-RL details

Drawings and details · 3/5

Cum se folosește

How it is used

ATZ 80150-RL



La capătul șirului, urmat de garduri modulare ATZ 80150-R

At the end of a run, followed by ATZ 80150-R modular barriers



4 garduri închid o zonă pe toate laturile

4 barriers close an area on all sides



Se stivuiesc culcate, pe palet

They stack flat on a pallet

ATZ 80150-RL: how it is used

Drawings and details · 4/5

Cu indicator și lampă
With a sign and a lamp

ATZ 80150-RL



Indicatorul și lampa se montează în cele 2 socluri filetate și se comandă separat
The sign and the lamp fit the 2 threaded sockets and are ordered separately



Indicator din plastic pe soclu
Plastic sign on the socket



Lampă solară ATZ 404-Y pe soclu
ATZ 404-Y solar lamp on the socket

ATZ 80150-RL with a plastic sign and an ATZ 404-Y lamp mounted on the sockets

Drawings and details · 5/5


Sistem de prindere: șurub ATZ 80A + diblu ATZ 90A

Fixing system: ATZ 80A screw + ATZ 90A dowel

ATZ 80A – Șurub Ø10 x 110 mm (DIN 571), cap hexagonal cu flanșă

ATZ 80A – Ø10 x 110 mm screw (DIN 571), hexagon flange head








ATZ 90A – Diblu Ø16 x 90 mm (secțiune A-A)

ATZ 90A – Ø16 x 90 mm dowel (section A-A)



Dimensiuni în mm. Gaura pentru diblu: Ø16 mm. Șurubul are 100 mm sub cap și 108,5 mm în total; diblul are 88 mm.

Dimensions in mm. Hole for the dowel: Ø16 mm. The screw is 100 mm under the head, 108.5 mm overall; the dowel is 88 mm long.

Câte un diblu și un șurub pentru fiecare punct de prindere al produsului.

One dowel and one screw for each fixing point of the product.

ATZ 80150-RL fixing system: ATZ 80A Ø10 × 110 mm screw and ATZ 90A Ø16 × 90 mm dowel