B2 Priority Sign – Stop, 60 cm, Class I

Class I (EGP) Road Signs | Signs compliant with SR 1848-1:2024



AT A GLANCE

- Priority sign B2 “Stop”, to SR 1848-1:2024.
- Red octagon 60 cm high, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	**B2**
Category	**Metal Road Signs**
Weight	**3 kg**
Compliance	**Class I (EGP) Road Signs**
Compliance	**Signs compliant with SR 1848-1:2024**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/indicator-b2-oprire-stop-60-cm-clasa-i

Technical specifications

SR 1848-1 code	B2
Name in the standard	Stop
Type	Priority road sign
Shape and colours	Red octagon, white border, white STOP legend
Size	60 cm high
Format (SR 1848-2)	Small
White border	7 mm
Legend	STOP, 225 mm letters
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges

Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	3 kg
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The B2, the red octagon with STOP, requires a full stop even if the road looks clear. It goes where drivers cannot see traffic on the priority road until they have stopped.

When class I is used

Class I (RA1) sheeting returns 70 cd/(lx·m²) for white to the driver and has a 7-year service life, enough on roads where headlights are the only light: local, minor and private roads or quiet streets. In areas with street lighting, shop windows, advertising and dense urban traffic, however, SR 1848-2 requires prismatic class 2 or 3 sheeting. The class II versions are the B2_80_II (80 cm) and the B2_II (100 cm).

Where it goes, under SR 1848-1:2024

It goes on the minor public road or cycle track, at junctions without good visibility, or where a cycle track or cycle road meets the carriageway, as close as possible to the edge of the priority road, but so that stopped vehicles do not block pedestrians crossing. It is also used at crossings with a railway without barriers, other than an industrial line, where it goes with the A47 or A48 cross. The B2 can be signed in advance with an identical sign and the P4 panel, showing the distance in metres to the edge of the road ahead.

At junctions, signs on the minor roads are placed so that their face cannot be seen from the priority road. At acute-angle junctions the sign is set back from the edge of the priority road; if it stands more than 10 m back, the P4 additional panel with the distance goes under it.

Technical data

- red octagon 60 cm high (small format, SR 1848-2), 7 mm white border and white STOP legend with 225 mm letters;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 3 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform. When they share a post, priority signs go above mandatory signs.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.


The 60 cm height is the small format in SR 1848-2, for low-traffic local roads and short-term police signing; it also suits private premises, car parks and yards. County and local roads, streets and private roads open to public traffic call for the normal 80 cm format: the B2_80_I.

Drawings and details · 1/3

B2 – Oprire

Stop

60 cm · dimensiunile feței indicatorului
60 cm · sign face dimensions



Dimensiuni SR 1848-2 (mm)
SR 1848-2 dimensions (mm)

60 cm
H = 600 · b = 7 · h = 225 · r = 30
drumuri vicinale cu trafic redus
low-traffic local access roads


80 cm
H = 800 · b = 9 · h = 300 · r = 30
drumuri județene, comunale, străzi
county and communal roads, streets

100 cm
H = 1000 · b = 11 · h = 375 · r = 30
drumuri naționale
national roads

120 cm
H = 1200 · b = 13 · h = 450 · r = 30
autostrăzi
motorways


Fond roșu, chenar alb b; cotele sunt ale feței retroreflectorizante.
Red background, white edge b; dimensions of the retroreflective face.
Panoul suport depășește fața cu 5–10 mm (SR 1848-2, 6.1).
The backing panel is 5–10 mm larger than the face (SR 1848-2, 6.1).
Colțurile se racordează cu raza r = 30 mm (SR 1848-2, 6.6).
Corners are rounded with radius r = 30 mm (SR 1848-2, 6.6).
H = înălțimea octogonului; spațiile S-T, T-O și O-P după tab. 7.
H = height of the octagon; S-T, T-O and O-P spacing as in table 7.
Formatul se alege după categoria drumului (SR 1848-2, 5.2).
The format follows the road category (SR 1848-2, 5.2).
Scriere SR 1848-3: tip „îngust”, H = 225 mm.
SR 1848-3 lettering: narrow type, H = 225 mm.
Sursa: SR 1848-2:2011, tab. 7.
Source: SR 1848-2:2011, table 7.

Drawings and details · 2/3



Drawings and details · 3/3

Prindere cu canal și colier, stâlp Ø48 mm
Channel and clamp fixing, Ø48 mm post



1 Canal de prindere din aluminiu (pe spatele panoului)
Aluminium fixing channel (on the back of the panel)

2 Șurub M8 × 35 cu cap pătrat, zincat (2 buc.)
M8 × 35 square-head bolt, galvanised (2 pcs)

3 Colier Ø48 mm din tablă zincată
Ø48 mm clamp, galvanised steel

4 Piuliță M8 zincată (2 buc.)
M8 nut, galvanised (2 pcs)

Set pentru un punct de prindere. Pentru stâlp Ø60 mm, colierele se livrează la cerere.
Set for one fixing point. Clamps for Ø60 mm posts are available on request.