
U21 Temporary Sign – Temporary Narrowing (Right Lane, 2 to 1), 80×120 cm, Class II

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Temporary road sign U21 "Temporary narrowing", to SR 1848-1:2024.
- 80×120 cm yellow panel with 2 lanes becoming 1, in 1 mm galvanised steel sheet.
- Class II (RA2) prismatic sheeting, guaranteed 10-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.

Product code	**U21_II**
Category	**Metal Road Signs (Class II)**
Weight	**10 kg**
Compliance	**Signs compliant with SR 1848-1:2024**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/indicator-u21-ingustare-temporara-banda-din-dreapta-2-in-1-80×120-cm-clasa-ii

Technical specifications

SR 1848-1 code	U21
Name in the standard	Temporary narrowing
Type	Temporary road sign
Shape and colours	80×120 cm yellow panel with 2 lanes becoming 1, with the right lane closed
Size	80×120 cm
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class II (RA2), prismatic, UV-resistant

Retroreflection (white, 0.2°/5°)	250 cd/(lx·m²)
Sheeting service life	10 years (SR 1848-2)
Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011
Marking	CE

Description

The 80×120 cm yellow panel showing that, of two lanes, the right one closes, with class II prismatic sheeting. It goes before works at the edge of the road, so drivers in the right lane can move over in good time.

Why class II

Class II (RA2) prismatic sheeting shows up three to four times better at night than class I sheeting, even among plant lights and street lights. For temporary signing, SR 1848-2 adds a clear rule: a temporary sign must have at least the retroreflection class of the permanent signs on the section, so on roads already signed in class II it is the compliant choice.

Where it goes, under SR 1848-1:2024

It shows drivers, before the work zone, which lane closes and where traffic continues. The content of the sign is chosen to match the road layout; this version shows 2 lanes becoming 1, with the right lane closed. SR 1848-1:2024 sets no specific distance for this sign: it is installed under the technical regulations in force for signing roadworks, following the signing layout of the works. Like any sign, it normally goes on the right-hand side of the direction of travel, so that it can be seen from at least 50 m in built-up areas and at least 100 m outside them (SR 1848-2).

What the roadworks rules require (Order 1112/411/2000)

The sign belongs to the advance signing, which is installed first, ahead of the work zone in the direction of travel, with at least 50 cm of clear space outside the carriageway. The rules require signs to be stood on the ground first, to check that they are clearly visible, and only then fixed to a support; no more than two signs go on the same support or side by side, and on one-way roads or bends they can be repeated on the left side or above the road.

On public roads, works are signed under the methodological rules approved by Order MI/MT no. 1112/411/2000. The road closure or traffic restriction is approved by the road authority, with the traffic police's agreement, on the basis of a signing layout endorsed as final, a copy of which the contractor keeps at the work site. The contractor installs, completes and maintains the signing for the whole job, removes it at the end and restores the original signing; accidents caused by incomplete or missing temporary signing are entirely the contractor's responsibility.

At night, if the existing signing on the road is retroreflective, the temporary signing must be retroreflective too and can be supplemented with flashing or sequential (“cascade”) amber lamps; on main and connecting streets in towns, retroreflective temporary signs are supplemented with flashing amber lamps.

Technical data

- 80×120 cm yellow panel with 2 lanes becoming 1, with the right lane closed;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted;
- class II (RA2) prismatic retroreflective sheeting, with a guaranteed 10-year service life;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform.

The 80×120 cm size is the one SR 1848-2 sets for national roads; motorways call for 120×180 cm, and other roads and streets for 65×85 cm. The class I sheeting version, 65×85 cm, is the U21.


Drawings and details · 1/3

U21 – Îngustare temporară

Temporary narrowing

80 x 120 cm · dimensiunile feței indicatorului

80 x 120 cm · sign face dimensions



Dimensiuni SR 1848-2 (mm)

SR 1848-2 dimensions (mm)

65 x 85 cm

650 x 850 · r = 30

străzi și alte drumuri

streets and other roads

80 x 120 cm

800 x 1200 · r = 30

drumuri naționale

national roads

120 x 180 cm

1200 x 1800 · r = 30

autostrăzi

motorways

Indicator temporar: fond galben; cotele sunt ale feței retroreflectorizante.

Temporary sign: yellow background; dimensions of the retroreflective face.

Panoul suport depășește fața cu 5–10 mm (SR 1848-2, 6.1).

The backing panel is 5–10 mm larger than the face (SR 1848-2, 6.1).

Colțurile se racordează cu raza r = 30 mm (SR 1848-2, 6.6).

Corners are rounded with radius r = 30 mm (SR 1848-2, 6.6).


U21: banda din dreapta, 2 în 1; U21a: 3 în 2.

U21: right lane, 2 into 1; U21a: 3 into 2.

Sursa: SR 1848-2:2011, tab. 12.

Source: SR 1848-2:2011, table 12.


Drawings and details · 2/3



Drawings and details · 3/3

Prindere cu profil de rigidizare și colier, stâlp Ø48 mm

Reinforcement rail and clamp fixing, Ø48 mm post



1 Profil de rigidizare din aluminiu (pe spatele panoului)
Aluminium reinforcement rail (on the back of the panel)

2 Șurub M8 × 35 cu cap pătrat, zincat (2 buc.)
M8 × 35 square-head bolt, galvanised (2 pcs)

3 Plăcuță anti-rotire din aluminiu (2 buc.)
Aluminium anti-rotation plate (2 pcs)

4 Colier Ø48 mm din tablă zincată
Ø48 mm clamp, galvanised steel

5 Piuliță M8 zincată (2 buc.)
M8 nut, galvanised (2 pcs)

Set pentru un punct de prindere. Pentru stâlp Ø60 mm, colierele se livrează la cerere.
Set for one fixing point. Clamps for Ø60 mm posts are available on request.