
# U22 Temporary Sign – Temporary Narrowing (Left Lane, 2 to 1), 65×85 cm, Class I

Class I (EGP) Road Signs | Signs compliant with SR 1848-1:2024



## AT A GLANCE

- Temporary road sign U22 "Temporary narrowing", to SR 1848-1:2024.
- 65×85 cm yellow panel with 2 lanes becoming 1, in 1 mm galvanised steel sheet.
- Class I (RA1) retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.

| | |
|---|---|
| Product code | **U22** |
| Category | **Metal Road Signs** |
| Weight | **5 kg** |
| Compliance | **Class I (EGP) Road Signs** |
| Compliance | **Signs compliant with SR 1848-1:2024** |

This product on attotrafic.ro
**https://attotrafic.ro/en_US/products/indicator-u22-ingustare-temporara-banda-din-stanga-2-in-1-65x85-cm-clasa-i**

## Technical specifications

| | |
|---|---|
| **SR 1848-1 code** | U22 |
| **Name in the standard** | Temporary narrowing |
| **Type** | Temporary road sign |
| **Shape and colours** | 65×85 cm yellow panel with 2 lanes becoming 1, with the left lane closed |
| **Size** | 65×85 cm |
| **Material** | Galvanised steel sheet, 1 mm |
| **Construction** | Rounded corners, pressed edges, no sharp edges |
| **Painting** | Electrostatic |
| **Retroreflective sheeting** | Class I (RA1) |

| | |
|---|---|
| **Retroreflection (white, 0.2°/5°)** | 70 cd/(lx·m²) |
| **Sheeting service life** | 7 years (SR 1848-2) |
| **Fixings included** | 2 clamps, 4 bolts with nuts |
| **Post diameter** | Ø48 mm (Ø60 mm on request) |
| **Standards** | SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011, SR 1848-3:2011 |

## Description

The 65×85 cm panel for works next to the centre of the road: of two lanes, the left one closes. It has class I retroreflective sheeting.

### When class I is used

Class I (RA1) retroreflective sheeting is the basic class in SR 1848-2, with a 7-year service life. For roadworks, the standard requires temporary signs to have at least the class of the permanent signing on the section, so the class I version is used where the existing signs are class I too, typically on county and local roads and on streets without strong lighting. For national roads, lit boulevards or sections signed in class II there is the U22_II version.

### Where it goes, under SR 1848-1:2024

It shows drivers, before the work zone, which lane closes and where traffic continues. The content of the sign is chosen to match the road layout; this version shows 2 lanes becoming 1, with the left lane closed. SR 1848-1:2024 sets no specific distance for this sign: it is installed under the technical regulations in force for signing roadworks, following the signing layout of the works. Like any sign, it normally goes on the right-hand side of the direction of travel, so that it can be seen from at least 50 m in built-up areas and at least 100 m outside them (SR 1848-2).

### What the roadworks rules require (Order 1112/411/2000)

The sign belongs to the advance signing, which is installed first, ahead of the work zone in the direction of travel, with at least 50 cm of clear space outside the carriageway. The rules require signs to be stood on the ground first, to check that they are clearly visible, and only then fixed to a support; no more than two signs go on the same support or side by side, and on one-way roads or bends they can be repeated on the left side or above the road.

On public roads, works are signed under the methodological rules approved by Order MI/MT no. 1112/411/2000. The road closure or traffic restriction is approved by the road authority, with the traffic police's agreement, on the basis of a signing layout endorsed as final, a copy of which the contractor keeps at the work site. The contractor installs, completes and maintains the signing for the whole job, removes it at the end and restores the original signing; accidents caused by incomplete or missing temporary signing are entirely the contractor's responsibility.

At night, if the existing signing on the road is retroreflective, the temporary signing must be retroreflective too and can be supplemented with flashing or sequential (“cascade”) amber lamps; on main and connecting streets in towns, retroreflective temporary signs are supplemented with flashing amber lamps.

### Technical data

- 65×85 cm yellow panel with 2 lanes becoming 1, with the left lane closed;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted;
- class I retroreflective sheeting (RA1), with a 7-year service life;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- compliant with SR EN 12899-1:2007, SR 1848-1:2024, SR 1848-2:2011 and SR 1848-3:2011.

### Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request. The bottom edge of the sign goes 1.50–2.50 m above the road or kerb, and the edge nearest the road 0.50–2.0 m from the road platform.

The 65×85 cm size is the one SR 1848-2 sets for county and local roads and streets; national roads call for 80×120 cm, and motorways for 120×180 cm. The class II sheeting version, 80×120 cm, is the U22_II.


## Drawings and details · 1/3

# U22 – Îngustare temporară

Temporary narrowing

65 x 85 cm · dimensiunile feței indicatorului

65 x 85 cm · sign face dimensions




**Dimensiuni SR 1848-2 (mm)**
SR 1848-2 dimensions (mm)

**65 x 85 cm**
650 x 850 · r = 30
străzi și alte drumuri
streets and other roads

**80 x 120 cm**
800 x 1200 · r = 30
drumuri naționale
national roads

**120 x 180 cm**
1200 x 1800 · r = 30
autostrăzi
motorways

Indicator temporar: fond galben; cotele sunt ale feței retroreflectorizante.
Temporary sign: yellow background; dimensions of the retroreflective face.


Panoul suport depășește fața cu 5–10 mm (SR 1848-2, 6.1).
The backing panel is 5–10 mm larger than the face (SR 1848-2, 6.1).

Colțurile se racordează cu raza r = 30 mm (SR 1848-2, 6.6).
Corners are rounded with radius r = 30 mm (SR 1848-2, 6.6).

U22: banda din stânga, 2 în 1; U22a: 3 în 2.
U22: left lane, 2 into 1; U22a: 3 into 2.

Sursa: SR 1848-2:2011, tab. 12.
Source: SR 1848-2:2011, table 12.


## Drawings and details · 2/3



## Drawings and details · 3/3

# Prindere cu canal și colier, stâlp Ø48 mm

Channel and clamp fixing, Ø48 mm post




**1** Canal de prindere din aluminiu (pe spatele panoului)
Aluminium fixing channel (on the back of the panel)

**2** Șurub M8 × 35 cu cap pătrat, zincat (2 buc.)
M8 × 35 square-head bolt, galvanised (2 pcs)

**3** Colier Ø48 mm din tablă zincată
Ø48 mm clamp, galvanised steel

**4** Piuliță M8 zincată (2 buc.)
M8 nut, galvanised (2 pcs)

Set pentru un punct de prindere. Pentru stâlp Ø60 mm, colierele se livrează la cerere.
Set for one fixing point. Clamps for Ø60 mm posts are available on request.