Distance to Stop Sign Panel, 30×30 cm, Class I

Class I (EGP) Road Signs



AT A GLANCE

- "Distance to Stop sign" panel, with the words STOP and 50m.
- 30 × 30 cm, in 1 mm galvanised steel sheet.
- Class I retroreflective sheeting, 7-year service life.
- Fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts.
- CE marked; sheeting and paint resistant to UV and weathering.

Product code	**ATT STOP**
Category	**Non-STAS**
Weight	**1.5 kg**
Compliance	**Class I (EGP) Road Signs**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/panou-distanta-pana-la-indicatorul-oprire-30×30-cm-clasa-i

Technical specifications

Type	Advance panel for premises and private roads
Shape and colours	White square with a black border and the black words STOP and 50m
Size	30 × 30 cm
Material	Galvanised steel sheet, 1 mm
Construction	Rounded corners, pressed edges, no sharp edges
Painting	Electrostatic, UV-resistant paint
Retroreflective sheeting	Class I (RA1), UV-resistant
Retroreflection (white, 0.2°/5°)	70 cd/(lx·m²)
Sheeting service life	7 years
Weight	1.5 kg

Fixings included	2 clamps, 4 bolts with nuts
Post diameter	Ø48 mm (Ø60 mm on request)
Standards	SR EN 12899-1:2007, SR 1848-2:2011
Marking	CE

Description

The white panel with a black border and the words STOP and 50m warns in good time that the Stop sign comes in 50 m, so drivers have time to slow down.

When class I is used

Class I (RA1) sheeting returns 70 cd/(lx·m²) for white to the driver and has a 7-year service life, enough on roads where headlights are the only light: local, minor and private roads or quiet streets. In areas with street lighting, shop windows, advertising and dense urban traffic, however, SR 1848-2 requires prismatic class 2 or 3 sheeting.

Where it goes

It goes on the road approaching the intersection, ahead of the Stop sign, at the distance written on the panel. It helps where the Stop sign cannot be seen from far away, for example after a bend, on premises or on private roads.

Technical data

- 30 × 30 cm panel: white square with a black border and the black words STOP and 50m;
- 1 mm galvanised steel sheet, with rounded corners and pressed edges, no sharp edges;
- electrostatically painted with UV-resistant paint;
- class I retroreflective sheeting (RA1), resistant to UV and weathering, with a 7-year service life;
- weight: 1.5 kg;
- fixings included: 2 clamps for Ø48 mm posts and 4 bolts with nuts;
- CE marked; sheet, sheeting and construction to SR EN 12899-1:2007 and SR 1848-2:2011.

Mounting and size

Fixings for the post are included: 2 clamps for Ø48 mm posts and 4 bolts with nuts; clamps for Ø60 mm posts are available on request.

The post is ordered separately. For a fixed installation in a concrete foundation: the galvanised Ø48 mm post, 300 cm. For temporary use, with no foundation: the Ø48 mm tripod post, 120 cm. On concrete or paving, where you cannot dig: the Ø60 mm flange post, 300 cm, bolted down; for it, ask for the Ø60 mm clamps when you order.

The panel measures 30 × 30 cm and has 2 fixing channels on the back, one for each clamp.

Drawings and details · 1/3

ATT STOP – Distanța până la indicatorul Oprire

Distance to Stop sign

30 x 30 cm · dimensiunile feței indicatorului

30 x 30 cm · sign face dimensions



Dimensiuni (mm) Dimensions (mm)
30 x 30 cm 300 x 300 · r = 30 panou adițional additional panel

Indicator în afara SR 1848-1:2024, după desenul nostru; cotele sunt ale produsului.
Sign outside SR 1848-1:2024, our own design; dimensions of the product.


Panoul suport depășește fața cu 5–10 mm (SR 1848-2, 6.1).
The backing panel is 5–10 mm larger than the face (SR 1848-2, 6.1).

Scriere SR 1848-3: tip „îngust”, H = 100 mm.
SR 1848-3 lettering: narrow type, H = 100 mm.

Colțurile se racordează cu raza r = 30 mm (SR 1848-2, 6.6).
Corners are rounded with radius r = 30 mm (SR 1848-2, 6.6).

ATT STOP dimensions


Drawings and details · 2/3



Back of the ATT STOP panel

Drawings and details · 3/3

Prindere cu canal și colier, stâlp Ø48 mm
Channel and clamp fixing, Ø48 mm post



1 Canal de prindere din aluminiu (pe spatele panoului)
Aluminium fixing channel (on the back of the panel)

2 Șurub M8 × 35 cu cap pătrat, zincat (2 buc.)
M8 × 35 square-head bolt, galvanised (2 pcs)

3 Colier Ø48 mm din tablă zincată
Ø48 mm clamp, galvanised steel

4 Piuliță M8 zincată (2 buc.)
M8 nut, galvanised (2 pcs)

Set pentru un punct de prindere. Pentru stâlp Ø60 mm, colierele se livrează la cerere.
Set for one fixing point. Clamps for Ø60 mm posts are available on request.

ATT STOP fixing system