Ballastable New Jersey Barrier, 100×40×70 cm, Black

Signs compliant with SR 1848-1:2024



AT A GLANCE

- Black polyethylene New Jersey barrier, 100 × 40 × 70 cm.
- 7 kg empty, 35 l inside for water or sand.
- Links with other V15 barriers; alternated with yellow (V15-Y) it makes a yellow-black line.
- Stackable.

Product code	**V15-BK**
Category	**Barriers**
Weight	**7 kg**
Compliance	**Signs compliant with SR 1848-1:2024**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/parapet-lestabil-tip-new-jersey-100×40×70-cm-negru

Technical specifications

Material	Polyethylene
Interior Volume	35 L
Color	Black
Weight when full	about 42 kg (with water)
Length with hook	111.5 cm
Holes on top	2 x Ø50 mm, for a sign post

Description

Black has two uses. On its own it is the most discreet colour: right for a private car park, an office building's yard or an entrance you want to close without it looking like a building site. Alternated with yellow V15-Y barriers, it makes a yellow-black warning line.

Technical data

- black polyethylene;
- 100 cm long, 40 cm wide, 70 cm high;
- 7 kg empty;
- 35 l inside, for water or sand.

How it links up

At the ends it has the linking system that attaches it to the next barrier, whatever its colour. That way you can build a continuous line of black barriers, or alternate them with another colour.

At night

A black barrier is hard to see in the dark. If the line stays on the road overnight, alternate it with yellow or white barriers and add warning lamps.

Storage

Once drained, it stacks with the other V15 barriers, in red (V15-R), white (V15-W) or yellow (V15-Y).

What the roadworks rules require (Order 1112/411/2000)

SR 1848-1:2024 provides the plastic barrier (V15) to mark off the work zone lengthwise or to separate the directions of traffic on roads with at least two lanes each way. In the work-zone signing layout, it belongs to the signing that marks the works, installed after the advance signing and before the end-of-restriction signing. The methodological rules approved by Order MI/MT no. 1112/411/2000 require that, where the existing signing is not retroreflective, the lengthwise edge of the work zone is also marked with steady or flashing amber lamps, such as the V8-Y or V8-YS.

The contractor installs the signing to the layout approved by the road authority with the traffic police's agreement, maintains and completes it for the whole job and removes it at the end; accidents caused by incomplete or missing temporary signing are entirely the contractor's responsibility.

Wind tunnel tested


The barrier was tested in a wind tunnel, empty and filled with water to the maximum level. Filled with water it weighs about 42 kg. On top it has 2 Ø50 mm holes for a sign post.

Drawings and details · 1/3

Dimensiuni **V15-BK**

Dimensions

mm



Corp 100 x 40 cm, 111,5 cm cu cârligul, 70 cm înălțime. Polietilenă, 7 kg gol, 35 l, aproximativ 42 kg plin cu apă.
Body 100 x 40 cm, 111.5 cm with the hook, 70 cm high. Polyethylene, 7 kg empty, 35 l, about 42 kg full of water.
Sus: dop de umplere și 2 găuri Ø50 mm pentru stâlpul unui indicator.
On top: filling cap and 2 Ø50 mm holes for a sign post.

V15-BK dimensions

Drawings and details · 2/3

Detalii **V15-BK**
Details




Sigla ATTO TRAFIC, turnată în corp, pe partea din față
ATTO TRAFIC logo moulded into the body, on the front




Dop de umplere, sus
Filling cap on top



Dop de golire, jos
Drain plug at the bottom



Cârlig de legătură cu parapetul vecin
Hook that links to the next barrier



Reper de nivel MAX
MAX level mark

V15-BK details

Drawings and details · 3/3

Cum se folosește

V15-BK

How it is used



Legați cap la cap, cu culorile alternate
Linked end to end, with alternating colours



Toate cele 4 culori se leagă între ele
All 4 colours link together



Goale, se stivuiesc
Empty, they stack

Se golește prin dopul de jos. Goale, ocupă mult mai puțin loc la transport și în depozit.
It drains through the bottom plug. Empty, they take up far less room in transport and storage.

V15-BK: how it is used