Flexible Delineator Post, PE, 30 cm, Orange

ECONOMIC



AT A GLANCE

- PE delineator post (economy), 30 cm, orange.
- One white honeycomb reflective band.
- Ø8 cm post, Ø20 cm round base, 0.45 kg.
- 3 anchors and 3 bolts included.

Product code	**ATZ 8030E**
Category	**Flexible Delineator Posts**
Brand	**Atto Trafic**
Weight	**0.45 kg**

This product on attotrafic.ro
https://attotrafic.ro/en_US/products/stalp-de-delimitare-flexibil-din-pe-30-cm-portocaliu

Technical specifications

Material	PE
Color	Orange
Height	30 cm
Post Diameter	Ø8 cm
Base Diameter	Ø20 cm
Base Shape	Round
Bellows Height	88 mm
Reflective	1 white honeycomb band, 64 mm
Installation	3 Ø16 × 90 mm dowels, 3 Ø10 × 110 mm screws
Fixing Holes	3 x Ø11 mm, on a Ø150 mm circle
Central Hole	Ø32 mm, along the post's axis

Description

A short, light post, only 0.45 kg, for places where you want to mark an edge without spending much: between parking bays, on car park islands, along cycle lanes or around pedestrian areas.

Material

It is made of PE (polyethylene), flexible and weather-resistant, with increased resistance to UV radiation. Compared with the TPU version, the ATZ 8030, it weighs less: 0.45 kg instead of 0.75 kg.

Visibility

It has one white honeycomb reflective band on the orange body, which shows up in the headlights.

Construction

Post and base are one piece. The 88 mm bellows at the bottom helps it straighten quickly after bending, and the hole along its axis, from top to bottom, keeps it from bursting when a car runs over it.

Size and installation

The post is 30 cm high and Ø8 cm, on a Ø20 cm round base. It is fixed straight into asphalt with 3 anchors and 3 bolts, supplied in the box.

Other PE posts

The economy PE series continues with the ATZ 8045E (45 cm), ATZ 8075E (75 cm) and ATZ 80100E (100 cm), all in orange, black or yellow.


Drawings and details · 1/3

ATZ 8030E – Stâlp delimitator flexibil din PE, 30 cm, portocaliu

ATZ 8030E Flexible delineator post, PE, 30 cm, orange


Ø80 x 300 mm · bază Ø200 mm · dimensiunile produsului

Ø80 x 300 mm · Ø200 mm base · product dimensions




Vedere de sus

Top view



Vedere de jos

Underside



Dimensiuni în mm. Stâlpul și baza sunt dintr-o singură bucată; burduful de jos are 88 mm.

Dimensions in mm. Post and base are one piece; the bellows at the bottom is 88 mm high.

PE, portocaliu, 0,45 kg; 1 bandă albă tip fagure de 64 mm.

PE, orange, 0.45 kg; 1 white honeycomb band, 64 mm wide.

Se prinde cu 3 dibluri Ø16 x 90 mm și 3 șuruburi Ø10 x 110 mm, incluse, prin găurile Ø11 mm ale bazei.

Fixed with 3 Ø16 x 90 mm dowels and 3 Ø10 x 110 mm screws, included, through the Ø11 mm holes of the base.

ATZ 8030E dimensions: Ø80 × 300 mm, Ø200 mm base, 88 mm bellows

Drawings and details · 2/3


Sistem de prindere: șurub ATZ 80A + diblu ATZ 90A

Fixing system: ATZ 80A screw + ATZ 90A dowel

ATZ 80A – Șurub Ø10 x 110 mm (DIN 571), cap hexagonal cu flanșă

ATZ 80A – Ø10 x 110 mm screw (DIN 571), hexagon flange head








ATZ 90A – Diblu Ø16 x 90 mm (secțiune A-A)

ATZ 90A – Ø16 x 90 mm dowel (section A-A)



Dimensiuni în mm. Gaura pentru diblu: Ø16 mm. Șurubul are 100 mm sub cap și 108,5 mm în total; diblul are 88 mm.

Dimensions in mm. Hole for the dowel: Ø16 mm. The screw is 100 mm under the head, 108.5 mm overall; the dowel is 88 mm long.

Câte un diblu și un șurub pentru fiecare punct de prindere al produsului.


One dowel and one screw for each fixing point of the product.

ATZ 8030E fixing system: ATZ 80A Ø10 × 110 mm screw and ATZ 90A Ø16 × 90 mm dowel

Drawings and details · 3/3


Montaj: 3 dibluri și 3 șuruburi, în asfalt sau beton

Installation: 3 dowels and 3 screws, in asphalt or concrete



Găurile în asfalt sau beton

Holes in the asphalt or concrete



1 Stâlpul și baza, dintr-o singură bucată. Baza e aceeași la toate înălțimile.
Post and base in one piece. The base is the same at every height.

2 Șurub ATZ 80A, Ø10 x 110 mm, prin gaura Ø11 mm a bazei, strâns în diblu.
ATZ 80A screw, Ø10 x 110 mm, through the Ø11 mm hole of the base, tightened into the dowel.

3 Diblu ATZ 90A, Ø16 x 90 mm, introdus până la nivelul suprafeței.
ATZ 90A dowel, Ø16 x 90 mm, pushed in level with the surface.

4 Asfalt sau beton: 3 găuri Ø16 mm, la 120°, pe un cerc Ø150 mm, la 130 mm una de alta.
Asphalt or concrete: 3 Ø16 mm holes, at 120°, on a Ø150 mm circle, 130 mm apart.

Installing ATZ 8030E: 3 dowels and 3 screws in asphalt or concrete